

## Sender box

### TS952

V1.2

Jan 2018

TS952 is a sender box with four network ports, and supports single, double and full color LED screen. It also supports 4K video source input and its maximum capability is 2.6 million pixels.

#### **1. Features:**

- 1) One Audio signal input;
- 2) One DVI video signal input;
- 3) One HDMI video signal input;
- 4) Supports 4K video source input;
- 5) Supports RCG file read-back function;
- 6) Supports RCG file broadcasting function;
- 7) Supports CON file broadcasting function;
- 8) Supports 12bit/10bit/8bit video input;
- 9) Supports 16bit grey scale;
- 10) With four network output ports, supports common video

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen  
Tel: +86-0755-33985098

source, like 2560x1024, 1920x1200, 2048x1152, etc;

11) Supported video format: RGB, YCrCb4:2:2, YCrCb4:4:4;

12) Supports cascade function;

13) Supports brightness auto-adjustment (requires light sensor).

## 2. Appearance



Interface introduction	
①	Power button/ indicator
②	Power input: AC100~240V
③	Indicator: red for power; green for signal
④	3.5mm audio input
⑤	USB connector for setup
⑥	HDMI signal input

⑦	DVI signal input
⑧	4 gigabit network ports
⑨	UART-IN: cascade input
⑩	UART-OUT: cascade output
⑪	Light sensor connector for brightness auto-adjustment

### 3. Working conditions

Rated power consumption(W)	20
Working temperature (°C)	-20°C ~ 75°C
Working humidity (%)	0% ~ 95%
Weight (KG)	3

**END**